Product Information



Universal Fleet Engine Oils

Gasoline & Diesel Engine Oils For Heavy Duty Applications Fleet Farm, Fleet, Off-Road All Purpose Oil API CI-4, CI-4 Plus, CH-4, CF / SL Ratings

DESCRIPTION

Xtreme[™] Universal Engine Oils are exceptionally versatile, premium quality, multi-grade crankcase lubricants giving outstanding performance in both diesel and gasoline engines in severe service and various operating conditions. Formulated using state-of-the-art additives and Group II base oils to meet current API and OEM requirements for volatility and oxidation resistance. Meets API level CI-4 or CI-4 Plus requirements for improved oxidation stability, soot control, roller follower wear limits and reduced aeration.

Xtreme Universal Engine Oils meets OEM specifications where API CI-4 and CI-4 Plus oil is recommended. Diesel CI-4 Plus oils have higher TBN and improved volatility for certain engine maker requirements. OEM approved additive system offers maximum engine protection under widely varying operating conditions.

APPLICATION

- Over-the-road fleets, municipal service and school district bus fleets
- Automobiles, light and medium duty trucks with diesel or gasoline engines
- Stationary engines powering pumps, generators and drilling rigs
- Construction and farm equipment such as tractors, dozers, front end loaders, excavators
- Logging equipment such as skidders, feller bunchers, harvesters, loaders

BENEFITS

- Full film lubrication at operating temperatures
- Excellent low temperature flow properties for startup and cold weather use
- Outstanding soot control for new egr engines
- Exceptional engine cleanliness
- Outstanding anti-wear, oxidation control and friction control



MARTIN LUBRICANTS, A Division of Martin Operating Partnership L.P.

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ www.martinlubricants.com

Product Information

API Diesel CI-4 Plus, CI-4, CH-4, CG-4, CF-4, CF **PERFORMANCE**

API Gasoline SL, SI, SJ, SH

E7 ACEA

US Military MIL-PRF-2104G

EO-N Premium Plus 03, EO-O Mack

Cummins CES 20081 **Detroit Diesel** 93K218 Renault VI RLD-3 Volvo VDS 4 Allison C-4

Caterpillar ECF-1A, ECF-2, ECF-3

European MAN 3275, EMA DHD-1, MB 228.3

TYPICAL PROPERTIES	Method	10W-30 CI-4 Plus	10W-40 CI-4 Plus	15W-40 CI-4 Plus	20W-50 Cl-4 Plus
API Gravity	D-4052	32.6	31.3	30.3	29.1
Specific Gravity at 15.6°C	D-1298	0.8623	0.8692	0.8745	0.8811
Viscosity, cSt at 40°C	D-445	59.7	94.3	99.2	178.9
Viscosity, cSt at 100°C	D-445	10.5	14.8	13.9	19.8
Viscosity Index	D-2270	166	164	142	127
Flash Point, COC °C (°F)	D-92	220 (428)	232 (450)	226 (439)	238 (460)
Pour Point, °C (°F)	D-97	-44 (-47)	-32 (-26)	-44 (-47)	-43 (-45)
Ash, % Sulphated	D-874	1.25	1.22	1.40	1.25
TBN	D-2896	10.5	10.5	11.6	10.0
ML Bulk Number		567883	574442	567867	588211

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

This engine oil's service level is in accordance with the latest version of SAE J300 Engine Oil Viscosity Classification and SAE J183 Engine Oil Performance and Engine Service Classification.

Health And Safety Information See separate Safety Data Sheets available on request.

Xtreme™ and Martin Lubricants™ are trademarks of Martin Lubicants. All other marks are property of their respective owners.



LEVELS

MARTIN LUBRICANTS, A Division of Martin Operating Partnership L.P. SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ www.martinlubricants.com