

Product No: 565829, 565837, 565845, 596334, 585117

DOT Brake Fluid

Automotive & Heavy-Duty DOT 3 Fluid; High Boiling Point for Extended Life; Compatible With All OEM DOT 3 or DOT 4 Fluids

Description

Unimark TM DOT 3 Brake Fluid is a high boiling formulation designed for service fill or complete fill of all passenger cars, light trucks, SUV's and heavy-duty equipment where DOT 3 fluids are required.

Unimark™ DOT 3 Brake Fluid has a high boiling point for extended service life under adverse conditions.



Unimark™ DOT 3 Brake Fluid is suitable for use with conventional drum or disc brake systems. This fluid is compatible with all DOT 3 and DOT 4 fluids.

Application

• For all passenger cars, light trucks, SUVs, or heavy-duty equipment where DOT 3 fluids are recommended.

Benefits

- Low moisture activity reduces corrosion and extends service life
- Compatible with all seals and metals found in braking systems
- Compatible with all DOT 3 and DOT 4 fluids
- Excellent service fill or complete fill fluid







PERFORMANCE RATING			
DOT	Type 3 Motor Vehicle Brake Fluid		
U.S. Government	Federal Motor Vehicle Safety Standard 116		
SAE	J1703		
ISO	4925		

TYPICAL PROPERTIES				
	Method	Range	Brake Fluid DOT 3	
Specific Gravity at 15.6°C	D-1298	1.03-1.06	1.05	
Viscosity, cSt at 40°C	D-445	Report	7.63	
Viscosity, cSt at 100°C	D-445	1.5 min	1.96	
Viscosity, cP @ -40°C	D-2983	1500 max	1235	
Flash Point, COC °C	D-92	118 min	133	
Original ERBP °C		243 min	257	
Wet ERBP °C		140 min	151	

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact Martin Technical Service Department.

Health and Safety Information: See separate Safety Data Sheets available on request.

Unimark[™] and Martin Lubricants[™] are trademarks of Martin Lubricants. All other marks are property of their respective owners.

